



## The new Datalogger MultiLog for Mobile Wheel Profile Measurement RPM



|       | Measured | Warn | Limit |
|-------|----------|------|-------|
| DM    | 1071.20  | --   | ---   |
| QR    | 10.82    | <    | 12.00 |
| SH    | 31.94    | <    | 35.00 |
| SD_SB | 32.57    | >=   | 24.00 |
| SE_SB | 32.53    | <    | 33.00 |

- Windows CE operating system
- 320x240 pixel graphic display
- Alphanumeric keyboard
- 4 individual allocable function keys
- Powerd by standard NiMH accu
- Integrated charging controller
- Network interface for fast datatransfer (TCP/IP)
- RS232 and USB interface
- Display of measured profile curve
- Color-coded check of limits

# Option Tablett-PC for Mobile Wheel Profile Measurement RPM



- Windows 10 Pro operating system
- Intel HD Graphics 520
- Outdoor display with the latest IPS $\alpha$  technology
- High-brightness 10.1" WUXGA display (1920 x 1200) with up to 800 cd / m<sup>2</sup>
- Capacitive 10-Finger Multi-Touch Screen + Digitizer
- Crash resistance up to a height of 180 cm \*
- Waterproof and dustproof (IP65) \*
- Up to 14 hours of battery life; The battery can be used by the user change
- Flexible configurable port (serial, LAN, microSD or USB 2.0)
- Lightweight design - weighs about 1.1 kg